



Automotive Gear Oil

(03/30/2015 edition)

Parts Plus Limited Slip Gear Oil meets the API GL-5 hypoid gear performance classification, and the features listed for hypoid gear multipurpose use. It contains limited-slip (LS) chemistry to prevent/reduce differential chatter as well as being formulated from the highest quality base oils and a new and improved GL-5 additive system.

TYPICAL INSPECTION DATA

	API Gravity	Flash Point, C.	Viscosity, cSt.		VI	Brookfield Viscosity, cP.			Pour Point, C
			@100C	@40C		@-40C	@-26C	@-12C	
Limited Slip MP Hypoid LS GL-5									
80W-90	27.5	230	14.90	148.0	100	-	<150,000	-	-36

Some performance levels are limited by viscosity grades. Please consult the Parts Plus Performance Application Chart, the Parts Plus Inspection Data Table for the appropriate product or contact your District Manager for more complete information and recommendations.

PERFORMANCE APPLICATION CHART

SPECIFICATIONS	Limited Slip MP Hypoid LS GL-5
API:	
GL-1	√
GL-2/3	√
GL-4	√
GL-5	√
MT-1	√
Mil-PRF-2105E	√
Mack GO-J	√
Mack GO-J Plus	-
Limited Slip:	
M2C119A	√
M2C154A	√
Outboards and Stern Drives	√