



Transmission Fluids

(03/30/2015 edition)

Parts Plus DX III/M is a premium multipurpose Automatic Transmission Fluid recommended for many transmission systems used throughout the world specifying DEXRON® III / Mercon ATF as well as Allison C-3 and C-4 fluids. DX III/M ATF is recommended for use in all transmissions, hydraulic systems, and power steering units manufactured by American, European, Korean, Japanese and other manufactures from around the world specifying DEXRON®III H/Mercon® and earlier DEXRON® / Mercon® type transmission fluids.

Parts Plus Ford Type F ATF is an excellent, durable and economical product that may be used wherever a 2-P or M2C33-F fluid is recommended or required. This fluid meets Allison C-3 specifications and may be used in certain hydraulic systems that require anti-wear hydraulic oil. Ford Type F fluid is recommended for use in all transmissions, hydraulic systems, and power steering units manufactured by American, European, Korean, Japanese and other manufactures from around the world specifying Ford Type F fluid type transmission fluids.

TYPICAL INSPECTION DATA

	API Gravity	Flash Point, C.	Viscosity, cSt @100C	Viscosity, cSt @40C	VI	Brookfield Viscosity	Pour Point, C
DX III-H/M ATF							
5W-20	32.5	190	7.10	34.6	170	<20,000	-49
Type F Fluid							
10W-20	31.5	190	7.40	35.8	165	<50,000	-46

Some performance levels are limited by viscosity grades. Please consult the Parts Plus Performance Application Chart, the Parts Plus Inspection Data Table for the appropriate product or contact your District Manager for more complete information and recommendations.