

# MATERIAL SAFETY DATA SHEET

**PRODUCT NAME: Overall Clearcoat**

**PRODUCT CODE: PPC 710**

Page 1

---

---

## Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

---

---

HMIS CODES  
Health 2  
Flammability 2  
Reactivity 0  
PPE G

**MANUFACTURER'S NAME:**

Collision Pro/ADN

**ADDRESS:**

3085 Fountainside Drive, Suite 210  
Germantown, TN 38138

EMERGENCY PHONE : (800) 424 - 9300  
INFORMATION PHONE : (901) 682-9090  
FAX NUMBER : (901) 682-9098

DATE PRINTED : 8/1/2012

---

---

## Section 2 -- COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

---

---

% by WT	CAS No.	INGREDIENT	UNITS	VAPOR PRESSURE
5 - 20%	108-65-6	Propylene Glycol Monomethyl Ether Acetate	ACGIH TLV N/E ACGIH STEL N/E OSHA PEL N/E OSHA STEL N/E	3.7
5 - 20%	79-20-9	Methyl Acetate	ACGIH TLV TWA: 200.000 PPM ACGIH STEL 250.000 PPM OSHA PEL TWA: 200.000 ppm OSHA STEL 250.000 PPM	162.70
< 1%	64742-89-8	Aliphatic Naphtha	ACGIH TLV TWA: 300 ppm OSHA PEL TWA: 300 ppm	5.2
5 - 20%	1330-20-7	Xylene	ACGIH TLV 150 ppm ACGIH STEL 150 ppm OSHA PEL 100 ppm OSHA STEL 150 ppm	9.5
5 - 20%	98-56-6	Parachlorobenzotrifluoride	ACGIH TLV N/E ACGIH STEL N/E OSHA PEL N/E OSHA STEL N/E	5.3
5 - 20%	100-41-4	Ethylbenzene	ACGIH TLV 100 ppm ACGIH STEL 125 ppm OSHA PEL 100 ppm OSHA STEL 125 ppm	1.333
< 1%	77-58-7	Dibutyltin Dilaurate	ACGIH TLV TWA: 0.1 mg/m3 ACGIH STEL 0.02 mg/m3; skin OSHA PEL TWA: 0.1 mg/m3 OSHA STEL N/E	<1.00
< 1%	96-48-0	Butyrolactone	ACGIH TLV N/E ACGIH STEL N/E OSHA PEL N/E OSHA STEL N/E	3.2
1 - 5%	624-54-4	Pentyl Propionate	ACGIH TLV 100 ppm ACGIH STEL 150 ppm OSHA PEL N/E OSHA STEL N/E	2

---

---

## Section 3 -- HAZARDS IDENTIFICATION

---

---

**ROUTES OF EXPOSURE**

**EYE CONTACT:**

Causes eye irritation. Redness, itching, burning sensation and visual disturbances may indicate excessive eye contact.

**SKIN CONTACT:**

May cause slight skin irritation. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

## MATERIAL SAFETY DATA SHEET

**PRODUCT NAME: Overall Clearcoat**

**PRODUCT CODE: PPC 710**

Page 2

**SKIN ABSORPTION:**

Skin absorption not expected to occur.

**INHALATION:**

Vapor and/or spray may be harmful if inhaled.

**INGESTION:**

Harmful if swallowed.

**SIGNS & SYMPTOMS OF OVEREXPOSURE:**

Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:**

Not applicable.

**CHRONIC OVEREXPOSURE EFFECTS:**

Avoid long-term and repeated contact. Repeated exposure to vapors above recommended exposure limits (see Section 8) may cause irritation of the respiratory system and permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. The effects of long-term, low level exposures to this product have not been determined. Safe handling of this material on a long-term basis should emphasize the prevention of all contact with this material to avoid any effects from repetitive acute exposures. See Section 11, of this MSDS for a detailed list of chronic health effects information available on individual ingredients in this product.

---

---

### Section 4 -- FIRST AID MEASURES

---

---

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists After use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available.

**EYE CONTACT:**

Remove contact lens and pour a gentle stream of warm water through the affected eye for at least 15 minutes. If irritation persists, contact a poison control center, emergency room, or physician as further treatment may be necessary.

**SKIN CONTACT:**

Run a gentle stream of water over the affected area for 15 minutes. A mild soap may be used if available. If any symptoms persist, contact poison control center, emergency room, or physician as further treatment may be necessary.

**INHALATION:**

Remove from area to fresh air. If symptomatic, contact a poison control center, emergency room or physician for treatment information.

**INGESTION:**

Gently wipe or rinse the inside of the mouth with water. Sips of water may be given if person is fully conscious. Never give anything by mouth to an unconscious or convulsing person. Do Not induce vomiting. Contact a poison control center, emergency room or physician right away as further treatment will be necessary.

---

---

### Section 5 -- FIRE FIGHTING MEASURES

---

---

FLASH POINT	LEL	UEL
N/D F	0.8	16.0

**EXTINGUISHING MEDIA:**

Use National Fire Protection Association (NFPA) Class B extinguishers (carbon dioxide, dry chemical, or universal aqueous film forming foam) designed to extinguish NFPA Class IB flammable liquid fires. Water spray may be ineffective. Water spray may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

**PROTECTION OF FIREFIGHTERS:**

Fire-fighters should wear self-contained breathing apparatus and full protective clothing.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**

Keep this product away from heat, sparks, flame, and other sources of ignition (i.e. pilot lights, electric motors, static electricity). Invisible vapors can travel to a source of ignition and flash back. Do not smoke while using this product. Keep containers tightly closed when not in use. Closed containers may explode when overheated. Do not apply to hot surfaces. Toxic gases may form when this product comes in contact with extreme heat. May produce hazardous decomposition products when exposed to extreme heat. Extreme heat includes, but not limited to, flame cutting, brazing, and welding.

# MATERIAL SAFETY DATA SHEET

**PRODUCT NAME: Overall Clearcoat**

**PRODUCT CODE: PPC 710**

Page 3

---

---

## Section 6 -- ACCIDENTAL RELEASE MEASURES

---

---

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:**

Provide maximum ventilation. Only personnel equipped with proper respiratory, skin, and eye protection should be permitted in the area. Remove all sources of ignition. Take up spilled material with sand, vermiculite, or other noncombustible absorbent material and place in clean, empty containers for disposal. Only the spilled material and the absorbent should be placed in this container.

---

---

## Section 7 -- HANDLING RELEASE MEASURES

---

---

**PRECAUTIONS TO BE TAKEN DURING HANDLING AND STORAGE:**

Vapors may collect in low areas. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting material may have the hazards of all of its parts. Containers should be grounded when pouring. Avoid free fall of liquids in excess of a few inches.

**STORAGE:**

Do not store above 120F (48 degrees C). Store large quantities in buildings designed and protected for storage of NFPA Class IB flammable liquids.

---

---

## Section 8 -- EXPOSURE CONTROLS / PERSONAL PROTECTION

---

---

**ENGINEERING CONTROLS:**

Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 8 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

**PERSONAL PROTECTIVE EQUIPMENT EYES:**

Wear chemical-type splash goggles when possibility exists for eye contact due to splashing or spraying liquid, airborne particles, or vapors.

**SKIN/GLOVES:**

Wear protective clothing to prevent skin contact. Apron and gloves should be constructed of: neoprene Rubber or butyl rubber. No specific permeation/degradation testing have been done on protective clothing for this product Recommendations for skin protection are based on infrequent contact with this product. For frequent contact or total immersion, contact a manufacturer of protective clothing for appropriate chemical impervious equipment. Clean contaminated clothing and shoes.

**RESPIRATOR:**

Overexposure to vapors may be prevented by ensuring proper ventilation controls, vapor exhaust or fresh air entry. A NIOSH-approved air purifying respirator with the appropriate chemical cartridges or a positive pressure, air-supplied respirator may also reduce exposure. Read the respirator manufacturer's instructions and literature carefully to determine the type of airborne contaminants against which the respirator is effective, its limitations, and how it is to be properly fitted and used. Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 2 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

**GENERAL HYGIENE-ESTABLISHED EXPOSURE LIMITS:**

If Threshold Limit Values (TLVs) have been established by ACGIH and OSHA they will be listed below. These limits are intended for use in the practice of industrial hygiene as guidelines of recommendations in the control of potential workplace health hazards. These limits are not a relative index of toxicity and should not be used by anyone without industrial hygiene training.

---

---

## Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

---

---

PRODUCT WEIGHT	8.648 lb/gal	1036 g/l
SPECIFIC GRAVITY	1.030	
BOILING POINT	0 - 662 F	-17 - 350 C
VOLATILES	60.4 % by wt	65.6 % by vol
EVAPORATION RATE	Same as ether	
VAPOR DENSITY	Heavier than air	
REGULATORY VOC	4.29 lb/gal	515 g/l
ACTUAL VOC	3.56 lb/gal	427 g/l

---

---

## Section 10 -- STABILITY AND REACTIVITY

---

---

**STABILITY:**

This product is normally stable and will not undergo hazardous reactions.

**CONDITIONS TO AVOID:**

None Known.

**MATERIAL SAFETY DATA SHEET**

**PRODUCT NAME: Overall Clearcoat**

**PRODUCT CODE: PPC 710**

Page 4

**INCOMPATIBLE MATERIALS:**

Avoid contact with strong alkalis, strong mineral acids, or strong oxidizing agents.

**HAZARDOUS POLYMERIZATION:**

None Known.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

Carbon monoxide, carbon dioxide, oxides of sulfur, oxides of barium, lower molecular weight polymer fractions.

**CHRONIC TOXICITY:**

Target Organs:

Spleen-None Known-Mutagen-Carcinogen-Kidney-Liver-  
Embryotoxin-Teratogen-Brain-Central nervous system-Lung

**MUTAGENICITY:**

This has not been tested for this product.

**REPRODUCTIVE:**

This has not been tested for this product.

=====  
**Section 11 -- TOXICOLOGICAL INFORMATION**  
=====

CAS No.	Ingredient Name				
108-65-6	Propylene Glycol Monomethyl	LC50	RAT	4HR	N/E
		LD50	RAT		8532 mg/kg
79-20-9	Methyl Acetate	LC50	RAT	4HR	N/E
		LD50	RAT		N/E
64742-89-8	Aliphatic Naphtha	LC50	RAT	4HR	3400 ppm4H
		LD50	RAT		8 ml/kg
1330-20-7	Xylene	LC50	RAT	4HR	5000 ppm
		LD50	RAT		4300 mg/kg
98-56-6	Parachlorobenzotrifluoride	LC50	RAT	4HR	22000 mg/l
		LD50	RAT		13000 mg/kg
100-41-4	Ethylbenzene	LC50	RAT	4HR	N/E
		LD50	RAT		3500 mg/kg
77-58-7	Dibutyltin Dilaurate	LC50	RAT	4HR	N/E
		LD50	RAT		175 mg/kg
96-48-0	Butyrolactone	LC50	RAT	4HR	N/E
		LD50	RAT		1540 mg/kg
624-54-4	Pentyl Propionate	LC50	RAT	4HR	15,000 ppm
		LD50	RAT		14 g/kg: Rat

=====  
**Section 12 -- ECOLOGICAL INFORMATION**  
=====

**POTENTIAL ENVIRONMENTAL EFFECTS:**

ECOTOXICITY: No Information Available

**ENVIRONMENTAL FATE:**

Mobility: No Information Available

BIODEGRADATION: No Information Available

BIOACCUMULATION: No Information Available

**PHYSICAL/CHEMICAL:**

HYDROLYSIS: No Information Available

PHOTOLYSIS: No Information Available

=====  
**Section 13 -- DISPOSAL CONSIDERATIONS**  
=====

**WASTE DISPOSAL METHOD**

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution. Provide maximum ventilation, only personnel equipped with proper respiratory and skin and eye protection should be permitted in the area. Take up spilled material with sawdust,

**MATERIAL SAFETY DATA SHEET**

**PRODUCT NAME: Overall Clearcoat**

**PRODUCT CODE: PPC 710**

Page 5

vermiculite, or other absorbent material and place in containers for disposal. Waste material must be disposed of in accordance with federal, state, provincial and local environmental control regulations. Empty containers should be recycled by an appropriately licensed reconditioner/salvager or disposed of through a permitted waste management facility. Additional disposal information is contained on the Environmental Data Sheet for this product.

---

---

**Section 14 -- TRANSPORT INFORMATION**

---

---

Proper Shipping Name: Consumer Commodity  
NOS Technical Name: ORM-D  
Hazard Class: N/A  
UN Number: N/A  
Packing Group: N/A

---

---

**Section 15 -- REGULATORY INFORMATION**

---

---

SARA 313: CAS No.	CHEMICAL/COMPOUND	% by WT
1330-20-7	Xylene	18.0
100-41-4	Ethylbenzene	5.3
624-54-4	Pentyl Propionate	4.0

**CALIFORNIA PROPOSITION 65**

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**TSCA CERTIFICATION:**

U.S. TSCA: This product and/or all of its components are listed on the U.S. TSCA Inventory or is otherwise exempt from TSCA Inventory reporting requirements.

---

---

**Section 16 -- OTHER INFORMATION**

---

---

**DISCLAIMER:**

Do not handle until the manufacturer's safety precautions have been read and understood. Regulations require that all employees be trained on Material Safety Data Sheets for all products with which they come in contact. While we believe that the data contained herein is accurate and derived from qualified sources, the data are not to be taken as a warranty or representation for which we assume legal responsibility. They are offered solely for your consideration, investigation, and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.

**MATERIAL SAFETY DATA SHEET**

**PRODUCT NAME: Overall Clearcoat**

**PRODUCT CODE: PPC 710**

Page 6

**ENVIRONMENTAL DATA SHEET**

All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

PRODUCT NUMBER  
PPC 710

PRODUCT NAME  
Overall Clearcoat

PRODUCT WEIGHT	SPECIFIC GRAVITY	FLASH POINT
8.648 lb/gal	1.030	0 - 327 F

VOLATILE INGREDIENTS NAME	CAS No.	CERC.	SARA 313 TC	HAPS 112	PCT by Wt	PCT by Vol
Xylene	1330-20-7	X	X	X	18.0	21.5
Ethylbenzene	100-41-4	X	X	X	5.3	6.4
Pentyl Propionate	624-54-4		X		4.0	4.8

**VOLATILE ORGANIC COMPOUNDS**

A. Coating Density	8.65 lb/gal	1037 g/l
B. Total Volatiles	60.4 % by wt	65.7 % by vol
Exempt Volatiles	19.2 % by wt	17.0 % by vol
Water	0.0 % by wt	0.0 % by vol
C. Organic Volatiles	41.2 % by wt	48.6 % by vol
D. Percent Non-Volatile	39.6 % by wt	34.4 % by vol
E. Regulatory VOC	4.29 lb/gal	515 g/l
Actual VOC	3.36 lb/gal	427 g/l
Solids	3.42 lb/gal	410 g/l

**WASTE DISPOSAL**

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. The addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.